



Coated Folding Boxboard with Kraft Back Cartulinas Estucadas Reverso Café

Basis Weight Gramaje TAPPI 410		Stiffness Taber 15° Rigidez TAPPI 489		Stiffness Taber 15° Rigidez TAPPI 489		Caliper Espesor TAPPI 411	
g/m ²	lb/MSF	gf - cm		mN x M		Pts	µm
		CD	MD	CD	MD		
180	37	28	56	2,7	5,5	11,0	280
200	41	40	80	3,9	7,8	12,4	315
225	46	54	108	5,3	10,6	14,4	365
245	50	65	136	6,4	13,3	15,7	400
260	53	79	163	7,7	16,0	17,1	435
275	56	95	197	9,3	19,3	18,3	465
295	60	120	250	11,8	24,5	20,1	510
305	62	127	268	12,5	26,3	20,9	530
325	67	152	319	14,9	31,3	22,2	565
345	71	187	391	18,3	38,3	24,2	615
365	75	210	448	20,6	43,9	25,8	655
390	80	250	532	24,5	52,2	28,0	710
+/-5%		-10%		-10%		+/-5%	

*Only as reference / Valores referenciales

Smoothness / Lisura **PPS (µm)**
TAPPI 555 1,0 + 0,5

Brightness / Blancura **Top (% GE)**
TAPPI 525 / ISO 2470 83 +2 -2

Cobb (1min) **Top (g/m²)**
TAPPI 441 ≤45

Cobb (2min) **Back (g/m²)**
TAPPI 441 ≤80

Moisture / Humedad **(%)**
TAPPI 412 6,5 - 9,5

Notes / Notas:

- 1.- Test climate 23+/-1°C and 50+/-2% RH, (TAPPI 402) / Las condiciones atmosféricas de los ensayos son 50 +/-2% de H.R y 23 +/- 1°C
- 2.- Tolerances based upon 95% confidence limits, (for pallets or reels) / Las tolerancias especificadas para cada uno de los ensayos se garantizan para el 95% del lote, ya sea en hojas o rollos en base a muestreo representativo.
- 3.- All specifications mentioned above may be subject to technical changes. / Todas las especificaciones aquí entregadas pueden ser sujetas a cambios técnicos.

Delivery specifications / Especificaciones de entrega

Sheets and reels cutting specifications*

Especificaciones de corte para pliegos y rollos*

		Min.	Máx.
Reels Rollos	Width / Ancho	20,5 in (520 mm)	94,5 in (2.400 mm)
	Diameter / Diámetro	47,2 in (1.200 mm)	70,8 in (1.800 mm)
	Core / Bobina	12 in (305 mm)	
Sheets Hojas	Width x Length	11,8 x 15,7 in	47,2 x 55,1 in
	Ancho x Largo	300 x 400 mm	1.200 x 1.400 mm
	Height / Altura	28,5 in (720 mm)	67,7 in (1.720 mm)

* For other dimensions please contact our offices.
* Para otros formatos consultar en nuestras oficinas.

Tolerances / Tolerancias:

Reel width / Ancho rollo	-39,4/+39,4 mills (-1/+ 1 mm)
Reel diameter / Diámetro de rollo	-196,9/196,9 mills (-5/+ 5 mm)
Running meters / Metros lineales	-1%
Number of sheets / Número de hojas	-1%
Sheet width / Ancho hoja	±19,7 mills (0,5 mm)
Sheet length / Largo hoja	±39,4 mills (1,0 mm)

* For dimension over 1.000 mm, the tolerance is 0,1%
* Para dimensiones mayores a 1.000 mm, la tolerancia es 0,1%

Cartulinas CMPC SpA

Agustinas 1343 Piso 5, Santiago Chile
Tel.: (56 2) 2441 2020 • Fax: (56 2) 2672 34 50
www.cartulinas-cmpc.com

Issued / Fecha de especificación:
July 2015 / Julio 2015



NCh 2861 (HACCP) upon request
NCh 2861 (HACCP) a pedido



Products promoted on this package are FSC® certified

The mark of responsible forestry

Look for FSC® certified products